

Blitzbinder®, round															
Made of branded polyethylene. Universal tie. Worldwide patent. Can be reopened over and over.															
Form A							Form B								
Article No.	"L" in mm ± 5 mm	"D" in mm ± 0,5 mm	Tensile strength in N, min.	Form	Natural	Red	Special colours	Article No.	"L" in mm ± 5 mm	"D" in mm ± 0,5 mm	Tensile strength in N, min.	Form	Natural	Red	Special colours
ABV 212	120	3.5	130	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	ABVS 230	290	8.7	420	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
ABW 214	140	3.9	170	A	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	ABV 232	320	4.4	230	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
ABV 218	180	3.5	150	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	ABV 250	500	5.7	250	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
ABV 224	240	3.9	180	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	ABVS 270	665	6.6	370	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

The Allplastik-Blitzbinder® quick fasteners made of premium quality polyethylene have a special closure which, when combined with a round profile, guarantees maximum strength and reliable closing and can also be opened again at any time. In addition to its function as a fastener, the dual closure design of the Allplastik-Blitzbinder® quick fasteners allow a hanging loop to be formed.

- Material: Polyethylene
- Design: ABV (2 engaging holes), ABW (1 engaging hole), ABVS (extra strong version)
- Colour: red, natural, blue, yellow, green, black, brown, purple, orange, pink, olive green
- Length: 120 to 665 mm
- Printing or laser engraving: possible
- Temperature resistance: from - 40°C to + 70°C
- Extraction force: 13 to 42 daN (kg)
- The raw materials from which the Allplastik-Blitzbinder® quick fasteners are made are FDA-compliant and comply with the following EU directives: 1935/2004/EU, 2023/2006/EU and as amended, 10/2011/EU (contact with foodstuffs) as amended. 94/62/EU (packaging waste) and as amended concerning the defined limits of heavy metals. 2002/95/EU (RoHS) and 2011/65/EU as amended. 1907/2006/EU (REACH).